

Application No. 09/945,483  
No. 66251

Attorney Docket

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of the claims in the application:

1. (Original) A method of increasing utilization of user link bandwidth for a code division multiple access communications system comprising the steps of:  
selecting a set of orthogonal complex codes each having a code length that is greater than a code length of an optimum real code and less than or equal to a spreading code length; and

transferring symbols across at least one of a plurality of user links to or from at least one of a corresponding plurality of user terminals wherein the symbols are represented by a corresponding one of the set of orthogonal complex codes.

2. (Original) The method of Claim 1 wherein the set of orthogonal complex codes is generated from a Kronecker tensor product given by formula:

$$C_{LXP} = A_L \otimes W_P$$

wherein

$C_{LXP}$  is a matrix of orthogonal complex codes wherein each of the orthogonal complex codes has a code length equal to  $L \times P$ ,

$L$  is a positive integer,

$P$  equals  $2^n$  where  $n$  equals a positive integer,

$W_P$  is a Walsh code matrix for a code length of  $P$ ,

$A_L$  is a matrix of coefficients  $a_{jk}$  wherein  $j$  is a row index equal to  $1 \dots L$ ,  $k$  is a column index equal to  $1 \dots L$ , and

$$a_{jk} = e^{j2\pi(j-1)(k-1)/L}$$

3. (Original) The system of Claim 1 wherein the corresponding one of the set of orthogonal complex codes has a code length of 12.

Application No. 09/945,483  
No. 66251

Attorney Docket

4. (Original) The system of Claim 1 wherein the spreading code has a code length of 12.

5. (Original) A code division multiple access communications system comprising:

- a base station;
- a geo-stationary platform;
- a feeder link coupled to the base station and the geo-stationary platform for transferring symbols between the base station and the geo-stationary platform;
- a plurality of user terminals; and
- a plurality of user links coupled respectively to the plurality of user terminals and to the geo-stationary platform for transferring symbols between the geo-stationary platform and at least one of the plurality of user terminals wherein the symbols are represented by at a corresponding one of a set of orthogonal complex codes having a code length that is greater than a code length of an optimum real code and less than or equal to a spreading code length.

6. (Original) The system of Claim 5 wherein the set of orthogonal complex codes is generated from a Kronecker tensor product given by:

$$C_{LXP} = A_L \otimes W_P$$

wherein

$C_{LXP}$  is a matrix of orthogonal complex codes wherein the at least one of the orthogonal complex codes has a code length equal to  $L \times P$ ,

$L$  is a positive integer,

$P$  equals  $2^n$  and  $n$  equals a positive integer,

$W_P$  is a Walsh code matrix for a code length of  $P$ ,

$A_L$  is a matrix of coefficients  $a_{jk}$ , where  $j$  is a row index equal to  $1 \dots L$ ,  $k$  is a

Application No. 09/945,483  
No. 66251

Attorney Docket

column index equal to  $1 \dots L$ , and

$$a_{jk} = e^{j2\pi(q-1)(k-1)/L}$$

7. (Original) The system of Claim 5 wherein the at least one of the set of orthogonal complex codes has a code length of 12.

8. (Original) The system of Claim 5 wherein the spreading code has a code length of 12.

9. (Original) A method of increasing utilization of user link bandwidth in a code division multiple access communications system comprising the steps of:  
selecting a spreading code length; and  
selecting a set of orthogonal complex codes each having a code length that is greater than a code length of an optimum real code and less than or equal to the spreading code length.

10. (Original) The method of Claim 9 further comprising the step of transferring symbols across a user link to or from a user terminal wherein the symbols are represented by a corresponding one of the set of orthogonal complex codes.